

IN THE CLAIMS:

The text of all pending claims (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~strikethrough~~. When strikethrough cannot easily be perceived, or when five or fewer characters are deleted, [[double brackets]] are used to show the deletion. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please retain the claims in their present form in accordance with the following:

1. (Previously Presented) A refrigerator, comprising:
 - a refrigerator compartment maintained at a predetermined refrigerator temperature;
 - a freezer compartment maintained at a predetermined freezer temperature;
 - a temperature controlled chamber provided in the refrigerator compartment, partitioned from a remainder of the refrigerator compartment;
 - a cool air inlet port to introduce cool air from the freezer compartment into the temperature controlled chamber;
 - a cool air outlet port to discharge the cool air from the temperature controlled chamber into the freezer compartment;
 - a cooling fan positioned adjacent to the cool air inlet port, to forcibly circulate the cool air from the freezer compartment to the temperature controlled chamber; and
 - an intake damper installed in the cool air inlet port to open and close the cool air inlet port, the intake damper comprising a thin plate that opens the cool air inlet port in response to the cool air flowing into the temperature controlled chamber when the cooling fan is operated, and closes the cool air inlet port in response to a stoppage of flow of the cool air when the cooling fan is stopped.
2. (Original) The refrigerator according to claim 1, wherein the temperature controlled chamber has an opening at a front, and comprises:
 - a rear insulation wall;
 - upper and lower insulation walls;
 - side insulation walls; and
 - a drawer to store food items movable through the front opening.
3. (Original) The refrigerator according to claim 2, wherein:
 - the refrigerator compartment and the freezer compartment are partitioned from each

other by a vertical partition wall arranged between the refrigerator and freezer compartments;
and

the cool air inlet port and the cool air outlet port are located in the vertical partition wall,
so that the cool air is circulated between the freezer compartment and the temperature
controlled chamber through the cool air inlet and outlet ports.

4-6. (Cancelled)

7. (Previously Presented) The refrigerator according to claim 1, further comprising:
a temperature sensor mounted in the temperature controlled chamber to control
operation of the cooling fan, operating the fan when a first temperature of the temperature
controlled chamber rises above a predetermined temperature, and stopping fan operation when
the first temperature reaches the predetermined temperature.

8. (Original) The refrigerator according to claim 7, wherein:
the predetermined temperature is between the predetermined refrigerator temperature
and the predetermined freezer temperature.

9. (Previously Presented) A refrigerator, comprising:
a refrigerator compartment;
a freezer compartment;
a chamber partitioned from the refrigerator and freezer compartments;
a fan to forcibly circulate air from the freezer to the chamber; and
a port to exchange air between the freezer compartment and the chamber, the port
comprising
an inlet port to introduce air from the freezer into the chamber,
an outlet port to discharge air from the chamber into the freezer, and
an intake damper that selectively opens and closes the inlet port by the flow of air,
without an additional drive device.

10. (Original) The refrigerator according to claim 9, wherein the chamber comprises:
a drawer that moves in and out of the chamber to store food items.

11. (Cancelled)

12. (Previously Presented) The refrigerator according to claim 9, wherein:

the fan is positioned adjacent to the inlet port.

13. (Original) The refrigerator according to claim 12, wherein:
the fan is positioned in the chamber.

14. (Original) The refrigerator according to claim 12, wherein:
the fan is positioned in the freezer.

15. (Previously Presented) The refrigerator according to claim 9, wherein:
the fan is positioned in the inlet port.

16. (Cancelled)

17. (Cancelled)

18. (Previously Presented) A refrigerator, comprising:
a refrigerator compartment;
a freezer compartment;
a chamber partitioned from the refrigerator and freezer compartments; and
a port to exchange air between the freezer compartment and the chamber, the port
comprising
 an inlet port to introduce air from the freezer into the chamber;
 an outlet port to discharge air from the chamber into the freezer
 a fan positioned adjacent to the inlet port to forcibly circulate air from the freezer
to the chamber, and
 an intake damper to selectively open and close the inlet port,
wherein the intake damper comprises a plate that opens and closes the inlet port in
response to air flow from the freezer.

19. (Original) The refrigerator according to claim 18, wherein:
the plate is hinged at a first end to rotate the plate to open and close the inlet port in
response to air flow from the freezer.

20. (Original) The refrigerator according to claim 18, wherein:
when the fan operates, air flows from freezer and moves the plate, thereby opening the
inlet port.

21. (Original) The refrigerator according to claim 20, wherein the chamber further comprises:

a temperature sensor that operates the fan when a sensed temperature is above a predetermined temperature.

22. (Original) The refrigerator according to claim 21, wherein:

the predetermined temperature is between a freezer temperature and a refrigerator temperature.

23. (Previously Presented) An apparatus with a refrigerator compartment and a freezer compartment, comprising:

a temperature controlled chamber, cooled by air from the freezer compartment, and maintained at a predetermined temperature between a temperature of the refrigerator compartment and a temperature of the freezer compartment;

an inlet port channeling the air from the freezer into the temperature controlled chamber;
and

an intake damper opening and closing the intake port by the flow of air, without an additional drive device.

24. (Cancelled)